



2SL-3

| 電気方式 主開閉器 合計容量 幹線サイズ | 回路 番号 | 分岐開閉器 | | | 電圧 (V) | 負荷容量 | | 附属 機器 | 備考 |
|--|----------|----------|-------|-----|-----------|------|-------|----------|------------|
| | | 2P | 1P | ELB | | 電灯 | コンセント | | |
| 1φ3W(L) 200/100v 225/125AT | ① | | 50/20 | | 100 | 680 | | ▲×2 | |
| | ② | | | | | 1320 | | | |
| | ③ | | | | | 590 | | | |
| | ④ | | | | | 1080 | | | |
| | ⑤ | | | | | 1440 | | | |
| | ⑥ | | | | | 1500 | | | |
| | ⑦ | | | | | 900 | | | |
| | ⑧ | | | | | 500 | | | |
| | ⑨ | | | | | 900 | | | |
| | ⑩ | | | | | 1560 | | | |
| | ⑪ | | | | | 960 | | | |
| | ⑫ | | | | | | | | 予備 |
| | ⑬ | | | | | | | | " |
| | ⑭ | | | | | | | | LT0 11,430 |
| TO. 15,530 (16,430) 1φ3W(G) 200/100v 225/125AT 100° | BS | 3P50/30A | | | | 900 | | | 2SL-4へ |
| | BS | 3P50/30A | | | | 900 | | | 2SL-5へ |
| | ① | | 50/20 | | 100 | | 750 | | |
| | ② | | | | | | 1050 | | |
| | ③ | | | | | | 600 | | |
| | ④ | | | | | | 300 | | |
| | ⑤ | | | | | | 600 | | |
| | ⑥ | | | | | | 700 | | FCU |
| | ⑦ | | | | | | 100 | | " |
| | ⑧ | | | | | | | | 予備 |
| | ⑨ | | | | | | | | " |
| | ⑩ | | | | | | | | " |
| | ⑪ | | | | | | | | CT0 4,100 |
| | ⑫ | | | | | | | | |
| DC100v 38° TO. 1,360 | ⑬ | | 50/20 | | 100 | 480 | | 4×2 | |
| | ⑭ | | | | | 660 | | | |
| | ⑮ | | | | | 360 | | | |
| | ⑯ | | | | | 720 | | | |
| | ⑰ | | | | | 720 | | | |
| | ⑱ | | | | | 1500 | | | |
| | ⑲ | | | | | 960 | | | 予備 |
| | ⑳ | | | | | | | | " |
| | ㉑ | | | | | | | | T/ユニット×1 |
| | ㉒ | | | | | | | | LT0 5,400 |
| | ㉓ | | | | | | | | |
| | ㉔ | | | | | | | | |
| | ㉕ | | | | | | | | |
| | ㉖ | | | | | | | | |
| DD 3B | ㉗ | | 50/20 | | 100 | 150 | | | |
| | ㉘ | | | | | 600 | | | |
| | ㉙ | | | | | 300 | | | |
| | ㉚ | | | | | 750 | | | |
| | ㉛ | | | | | 300 | | | |
| | ㉜ | | | | | 450 | | | |
| | ㉝ | | | | | 600 | | | |
| | ㉞ | | | | | 300 | | | |
| | ㉟ | | | | | 200 | | | 表示板 |
| | ㊱ | | | | | 150 | | | 端子賢用 |
| | ㊲ | | | | | | | | 予備 |
| | ㊳ | | | | | | | | " |
| | ㊴ | | | | | | | | " |
| | ㊵ | | | | | | | | " |
| | ㊶ | | | | | | | | CT0 3,800 |
| | ㊷ | | | | | | | | 2SL-4へ |
| | BS | | | | | | 8900 | | |
| | ㊸ | | 50/20 | | 100 | 600 | | | |
| | ㊹ | | | | | 760 | | | 予備 |
| | ㊺ | | | | | | | | " |